NSN 5935-01-130-7651

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-130-7651 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.320 inches **Overall Diameter:** 0.870 inches **Cable Entrance Diameter:** 0.148 inches **Mounting Facility Thickness:** 0.250 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity:** 1 **Contact Position Arrangement Style:** Nonstd single mating end **Contact Removability:** Nonremovable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Bayonet pin **Connector Cable Strain Relief Method:** Compression nut Radio Frequency Type Contact Characteristic Impedance In Ohms: 95.0 single mating end single contact grouping Thready Qty Per Inch (tpi): **Thread Size:** 0.562 inches **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Terminal Type:**

Solder well single mating end single contact grouping

Included Contact Quantity:

1 single mating end single contact grouping

NSN 5935-01-130-7651

Electrical Receptacle Connector - Page 2 of 2



Bushing Accommodation Hole Shape:
Round w/flat
Included Contact Type:
Triaxial socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.005 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A039b0