## NSN 5935-01-130-8432

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-130-8432

**Body Style:** Straight shape, internal coupling Overall Length: 1.203 inches **Overall Diameter:** 1.344 inches **Environmental Protection:** Moisture proof and salt water resistant and vibration proof **Mating End Quantity: Contact Position Arrangement Style:** 27-13 single mating end **Contact Removability:** Nonremovable single mating end all contact groupings **Contact Maximum Ac Voltage Rating In Volts:** 600.0 single mating end all contact groupings **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Friction Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end 1st contact grouping **Terminal Location:** Back single mating end all contact groupings **Contact Material:** Copper alloy single mating end all contact groupings **Contact Surface Treatment:** Gold single mating end all contact groupings and copper single mating end all contact groupings **Terminal Type:** Solder well single mating end all contact groupings **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Chromate **Shell Material Specification:** Qq-a-591 federal specification single material response **Included Contact Quantity:** 

3 single mating end 1st contact grouping

## NSN 5935-01-130-8432

Electrical Plug Connector - Page 2 of 2



| ın | ادام | ided | 0 | nto | ~+ | т., | -   |
|----|------|------|---|-----|----|-----|-----|
| m  | CIU  | ıaea |   | mta | Ct | ıν  | De: |

Round socket single mating end 2nd contact grouping

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.027 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0