# NSN 5935-01-130-8432

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-130-8432

## **Body Style:**

Straight shape, internal coupling

## **Overall Length:**

1.203 inches

# **Overall Diameter:**

1.344 inches

### **Environmental Protection:**

Moisture proof and salt water resistant and vibration proof

## Mating End Quantity:

1

# **Contact Position Arrangement Style:**

27-13 single mating end

# Contact Removability:

Nonremovable single mating end all contact groupings

# Contact Maximum Ac Voltage Rating In Volts:

600.0 single mating end all contact groupings

### **Polarization Method:**

Keyway or multiple keyway

## Insert Position In Deg:

0.0

## Shell Type:

Solid

### **Connector Locking Method:**

Friction

# Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end 1st contact grouping

### **Terminal Location:**

Back single mating end all contact groupings

### **Contact Material:**

Copper alloy single mating end all contact groupings

### **Contact Surface Treatment:**

Gold single mating end all contact groupings and copper single mating end all contact groupings

### **Terminal Type:**

Solder well single mating end all contact groupings

### Shell Material:

Aluminum alloy

# Shell Surface Treatment:

Chromate

## **Shell Material Specification:**

Qq-a-591 federal specification single material response

## **Included Contact Quantity:**

3 single mating end 1st contact grouping

NSN 5935-01-130-8432

Electrical Plug Connector - Page 2 of 2



Included Contact Type: Round socket single mating end 2nd contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.027 gold grains, troy **Precious Material:** Gold Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A039b0