## NSN 5935-01-131-6814

**Body Style:** Straight type **Overall Length:** 

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-131-6814

_
1.810 inches
Overall Height:
0.390 inches
Overall Width:
0.118 inches
Environmental Protection:
Corrosion resistant
Unthreaded Mounting Hole Diameter:
0.115 inches
Distance Between Mounting Facility Centers:
1.520 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
1200.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Terminal Location:
Back single mating end single contact grouping
Contact Material:

Gold single mating end single contact grouping

Copper alloy single mating end single contact grouping

#### **Insert Material:**

Plastic diallyl phthalate single mating end

### **Terminal Type:**

Solder well single mating end single contact grouping

### **Insert Material Specification:**

**Contact Surface Treatment:** 

Mil-m-14, ty sdg-f military specification single material response single mating end

### **Included Contact Quantity:**

12 single mating end single contact grouping

### **Included Contact Type:**

Round pin single mating end single contact grouping

# NSN 5935-01-131-6814

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:	
Contact surfaces gold	
Precious Material And Weight:	
0.012 gold grains, troy	
Precious Material:	
Gold	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A039b0	

Mil-std (military Standard):

Mil-m-14 spec.