

View Online at <https://aerobasegroup.com/nsn/5935-01-131-7598>

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Body Style:**

Angle shape w/cable clamp

**Overall Diameter:**

1.469 inches

**Body Angle In Deg:**

90.0

**Cable Entrance Diameter:**

Between 0.350 inches and 0.625 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

20-4 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Connector Locking Method:**

Internally threaded coupling ring

**Connector Cable Strain Relief Method:**

Cable clamp

**Distance From Centerline To Connector End:**

2.875 inches

**Distance From Centerline To Cable End:**

3.438 inches

**Thready Qty Per Inch (tpi):**

18

**Thread Size:**

1.250 inches

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Aluminum

**Included Contact Quantity:**

4 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Thread Series Designator:**

Unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-c-5015 spec.