

View Online at <https://aerobasegroup.com/nsn/5935-01-132-1560>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Straight shape, internal coupling w/strain relief

Body Length:

4.250 inches

Overall Diameter:

1.688 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration proof

Cable Entrance Diameter:

Between 0.562 inches and 0.937 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

"18-8, 22-404" single mating end

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

41.0 single mating end 1st contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end all contact groupings

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end all contact groupings

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling ring

Connector Cable Strain Relief Method:

Cable clamp

Thready Qty Per Inch (tpi):

20

Thread Size:

1.000 inches

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings and nickel single mating end all contact groupings

Insert Material:

Rubber single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 1, grade b military specification 1st treatment response single mating end all contact groupings and qq-n-290, cl 1, grade b federal specification 2nd treatment response single mating end all contact groupings

Terminal Type:

Solder well single mating end all contact groupings

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Included Contact Quantity:

7 single mating end 2nd contact grouping

Included Contact Type:

Round pin single mating end all contact groupings

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.012 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.