Electrical Connector Backshell - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5935-01-132-7703

| Thread Class: 2b Thread Direction: Right-hand Seal Material: Rubber, silicone base Overall Height: 1.551 inches Overall Width: 1.551 inches Cobie Opening Oiameter: 1.550 inches Cable Opening Oiameter: Between 0.437 inches and 0.750 inches Cable Opening Ouantity: 1.250 inches Cable Opening Ouantity: 1 Seal Type: Grommet Seal Type: Grommet Seal Type: Grommet Size Designation: 20 Mounting Facility Type And Quantity: 1 threaded coupling Thread Y Per Inch (tpi): 18 Thread Size: 1.188 inches Material: Aluminum alloy Surface Treatment: Cadmium and nickel Style Designator: Straight type wicable clamp Straight type wicable clamp Cadmium and nickel Style Designator: Cadmium and nickel Style Designator: Cadmium and nickel Style Designator: Cadmium and nickel Thread Series Designator: Unef Sheft Life: Na Material: Aluminum and Messure: | | |
|--|---------------------------------------|--|
| Thread Direction: Right-hand Seal Material: Rubber, sillicone base Overall Meight: 1.551 Inches Overall Widht: 1.250 Inches Cable Opening Diameter: Between 0.437 Inches and 0.750 Inches Cable Opening Quantity: 1 Seal Type: Grommet Seal Type: 10 Seal Type: 11 Seal Type: 120 Mounting Facility Type And Quantity: 11 Thread State: 1.188 Inchead Coupling Thread State: 1.188 State Designation: 1.188 Inchead State: 1.188 State Designator: 1.188 Straight type w/cable clamp Interd Strees Designator: Interd Strees Design | | |
| Right-hand Seal Material: Rubber, silicone base Overall Height: 1.551 inches Overall Width: 1.551 inches Overall Width: 1.250 inches Cable Opening Diameter: Between 0.437 inches and 0.750 inches Cable Opening Quantity: 1 Seal Type: Grommet Size Designation: 20 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 18 18 Incheads: 118 inches Material: Aturnium alloy Surface Treatment: Cadmium and nickel Stringht type wicable clamp Surface Treatment: Cadmium and nickel Thread Series Stringht type wicable clamp Buttrate: Inter Generee: Cadmium and nickel Thread Series Designator: Under Cadmium and nickel Thread Series Designator: Inter Generee: Na Diff Measure: Na Diff Measure: Na Diff Measure: Na Diff Measure: Na Step Designator: Na Step Designator: Step Designator: Diff Measure: Na Diff Measure: Na Diff Measure: Na | | |
| Sel Material: Rubber, silicone base Overall Height: 1.551 inches Overall Width: 1.250 inches Cable Opening Diameter: Between 0.437 inches and 0.750 inches Cable Opening Quantity: 1 Sel Type: Grommet Size Designation: 20 Mounting Facility Type And Quantity: 1 threaded coupling Thready Oty Per Inch (tpi): 18 Interaded coupling Threaded Size: 1.188 inches Material: Aluminum alloy Surface Treatment: Cadmium and nickel Strike Thread Size: Strike Thread Size: Cadmium and nickel Surface Treatment: Cadmium and nickel Strike Thread Size: Strike Thread Size: Strike Thread Size: Strike Thread Size: Other Thread Size: Opening Called Camp Strike Thread Size: Strike Thread Size: Stright type wicable camp | | |
| Rubber, silicone base Overall Height: 1.551 inches Overall Width: 1.250 linches Cable Opening Diameter: Between 0.437 linches and 0.750 linches Cable Opening Quantity: 1 Seal Type: Grommet Size Designation: 20 Mounting Facility Type And Quantity: 1 threaded coupling Thread Q type Inch (tpi): 18 Thread Size: 1.188 linches Material: Aluminum alloy Surface Treatment: Cadmium and nickel Style Designator: Straight type wicable clamp Surface Treatment: Cadmium and nickel Thread Size: Outfor Measure: Cadmium and nickel Thread Series Designator: Via Material: Na Dired Measure: Cadmium and nickel Thread Series Designator: Na Stright Type Micable clamp Stright Type Micable clamp </th <th></th> <th></th> | | |
| Overall Height:1.551 inchesOverall Width:1.250 inchesCable Opening Diameter:Between 0.437 inches and 0.750 inchesCable Opening Quantity:Cable Opening Quantity:1Seal Type:GrommetSize Designation:20Monting Facility Type And Quantity:1 threaded couplingThread Y Qty Per Inch (pi):18Thread Size:1.188 inchesMurrinum alloySurface Treatment:Cadmium and nickelStright type websile dampSurface Treatment:Cadmium and nickelThread Series Designator:UnefShift Life:NaDired Measure:Cadmium and nickelSurface Treatment:Cadmium and nickelThread Series Designator:NaDirefShift Life:NaThread Series Designator:NaSurface Treatment:NaSurface Treatment:DirefShift Life:NaDirefShift Life:NaNaDirefShift Life:NaDirefShift Life:NaDirefShift Life:NaDirefShift Life:NaDirefShift Life:NaShift Life:NaShift Life:Na <tr< td=""><td></td><td></td></tr<> | | |
| 1.551 inches Overall Width: 1.250 inches Cable Opening Diameter: Between 0.437 inches and 0.750 inches Cable Opening Quantity: 1 Seal Type: Grommet Size Designation: 20 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 18 Thread Size: 1.188 inches Material: Aluminum alloy Surface Treatment: Cadmium and nickel Style Designator: Unef Shef Life: Na Unit of Measure: Life Na Derificatization: Na Denilitarization: Na Surface Treatment: Cadmium and nickel Thread Series Designator: Na Unit of Measure: Na Straight type wickels champ Straight type wickels champ Straight type wickels champ | | |
| Overall Width:1.250 inchesCable Opening Diameter:Between 0.437 inches and 0.750 inchesCable Opening Quantity:1Cable Opening Quantity:1Seal Type:GrommetSize Designation:20Mounting Facility Type And Quantity:1 threaded couplingThready Qty Per Inch (tpi):18Thread Size:1.188Material:Aluminum alloySurface Treatment:Cadmium and nickelStyle Designator:Cadmium and nickelThread Stres:Intrady type Wcable clampGuring and nickelStyle Designator:Cadmium and nickelThread Stres:Indif (the Size)Cadmium and nickelStyle Designator:UnofStreight Type Wcable clampCadmium and nickelThread Stres:Indi (the Size)Indi (the Size)Streight Type Wcable clampIndi (the Size)Streight Type Wcable clampIndi (the Size)Streight Type Wcable clampIndi (the Size)Indi (the Size)MaIndi (the Size)Indi | | |
| 1.250 inches Cable Opening Diameter: Between 0.437 inches and 0.750 inches Cable Opening Quantity: 1 Seal Type: Grommet Size Designation: 20 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 18 Thread Size: 1.188 inches Material: Aluminum alloy Surface Treatment: Cadmium and nickel Style Designator: Straight type wicable clamp Surface Treatment: Cadmium and nickel Thread Size: Naterial: Naterial: Straight type wicable clamp Surface Treatment: Cadmium and nickel Thread Series Designator: Naterial: Naterial: Naterial: Naterial: Diet Iffe: Naterial: Straight type wicable clamp Straight type wicable clamp Diet Iffe: Naterial: | | |
| Cable Opening Diameter: Between 0.437 inches and 0.750 inches Cable Opening Quantity: 1 Seal Type: Grommet Size Designation: 20 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 18 Thread Size: 1.188 inches Material: Aluminum alloy Surface Treatment: Cadmium and nickel Style Designator: Cadmium and nickel Stratestres Designator: Cadmium and nickel Stratestres Designator: Unef Shelf Life: Na Unit of Measure: - - Penilitarization: No Fig: | Overall Width: | |
| Between 0.437 inches and 0.750 inches Cable Opening Quantity: 1 Seal Type: Grommet Size Designation: 20 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 18 Thread Size: 1.188 inches Material: Aluminum alloy Surface Treatment: Cadmium and nickel Style Designator: Unef Striaght type w/cable clamp Striaght type w/cable clamp Cadmium and nickel Thread Sries Designator: Unef Sheff Life: N/a Unit Of Measure: - Pemilitarization: No | 1.250 inches | |
| Cable Opening Quantity: 1 Seal Type: Grommet Size Designation: 20 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 18 Thread Size: 1.188 inches Material: Aluminum alloy Surface Treatment: Cadmium and nickel Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium and nickel Straight type w/cable clamp Burface Treatment: Cadmium and nickel Straight type w/cable clamp Burface Treatment: Cadmium and nickel Straight type w/cable clamp Durface Treatment: Cadmium and nickel Thread Series Designator: Unef Duef Na Duef Na Duef Strift Life: Na Duef Fig: | Cable Opening Diameter: | |
| 1 Seal Type: Grommet Size Designation: 20 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 18 Thread Size: 1.188 inches Material: Aluminum alloy Surface Treatment: Cadmium and nickel Style Designator: Cadmium and nickel Style Designator: Cadmium and nickel Strafee Treatment: Cadmium and nickel Style Designator: Cadmium and nickel Thread Series Designator: Unef Shelf Life: Na Dut of Measure: Tot of Measure: Tot Themiltarization: No Fig: | Between 0.437 inches and 0.750 inches | |
| Seal Type:GrommetSize Designation:20Mounting Facility Type And Quantity:1 threaded couplingThready Qty Per Inch (tpi):18Thread Size:1.188 inchesMaterial:Aluminum alloySurface Treatment:Cadmium and nickelStyle Designator:Straight type w/cable clampSurface Treatment:Cadmium and nickelStraight type w/cable clampSurface Treatment:Cadmium and nickelThread Series Designator:UnefShelf Life:NaUnefShelf Life:NaDenilitarization:NaFig:Fig: | Cable Opening Quantity: | |
| Grommet Size Designation: 20 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 18 Thread Size: 1.188 inches Material: 1.188 inches Material: Aluminum alloy Surface Treatment: Cadmium and nickel Style Designator: Strlaght type w/cable clamp Surface Treatment: Cadmium and nickel Thread Series Designator: Unof Sheff Life: N/a Unit Of Measure: Demilitarization: No Fig: | 1 | |
| Size Designation: 20 Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpl): 18 Thread Size: 1.188 inches Material: Aluminum alloy Surface Treatment: Cadmium and nickel Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium and nickel Style Designator: Unef Shef Life: N/a Unit Of Measure: Demilitarization: No Fig: | Seal Type: | |
| 20 Mouting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 18 Thread Size: 1.188 inches Material: Aluminum alloy Material: Aluminum alloy Surface Treatment: Cadmium and nickel Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium and nickel Surface Treatment: C | Grommet | |
| Mounting Facility Type And Quantity: 1 threaded coupling Thready Qty Per Inch (tpi): 18 Thread Size: 1.188 inches Material: Aluminum alloy Surface Treatment: Cadmium and nickel Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium and nickel Straight type w/cable clamp Straface Treatment: Cadmium and nickel Straface Treatment: Cadmium and nickel Straface Treatment: Cadmium and nickel Durief Straface Treatment: Cadmium and nickel Thread Series Designator: Unef Shelf Life: N/a Dit Of Measure: Tread Theolitarization: No Fig: | Size Designation: | |
| 1 threadd coupling Thready Qty Per Inch (tpi): 18 Thread Size: 1.188 inches Material: Aluminum alloy Surface Treatment: Cadmium and nickel Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium and nickel Straight type w/cable clamp Surface Treatment: Cadmium and nickel Straight type w/cable clamp Surface Treatment: Cadmium and nickel Thread Series Designator: Unef Shelf Life: N/a Dit Of Measure: Themalitarization: No Fig: | 20 | |
| Thready Qty Per Inch (tpi): 18 Thread Size: 1.188 inches Material: Aluminum alloy Surface Treatment: Cadmium and nickel Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium and nickel Straight type w/cable clamp Straight type w/cable clamp Surface Treatment: Cadmium and nickel Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: | Mounting Facility Type And Quantity: | |
| 18 Thread Size: 1.188 inches Material: Aluminum alloy Surface Treatment: Cadmium and nickel Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium and nickel Straight type w/cable clamp Straight type w/cable clamp Surface Treatment: Cadmium and nickel Thread Series Designator: Unef Shelf Life: N/a Third Measure: Pomilitarization: No Fig: | 1 threaded coupling | |
| Thread Size: 1.188 inches 1.188 inches Material: Aluminum alloy Surface Treatment: Cadmium and nickel Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium and nickel Cadmium and nickel Cadmium and nickel Sheff Life: N/a Unef Sheff Life: N/a Unit Of Measure: Demiltarization: No Fig: | Thready Qty Per Inch (tpi): | |
| 1.188 inches Material: Aluminum alloy Aufrace Treatment: Cadmium and nickel Style Designator: Straight type w/cable clamp Straight type w/cable clamp Cadmium and nickel Cadmium and nickel Cadmium and nickel Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Temilitarization: No Fig: | 18 | |
| Material:Aluminum alloySurface Treatment:Cadmium and nickelStyle Designator:Straight type w/cable clampSurface Treatment:Cadmium and nickelThread Series Designator:UnefShelf Life:N/aUnit Of Measure:Demilitarization:NoFig: | Thread Size: | |
| Aluminum alloy Surface Treatment: Cadmium and nickel Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium and nickel Cadmium and nickel Cadmium and nickel Chread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: | 1.188 inches | |
| Surface Treatment: Cadmium and nickel Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium and nickel Cadmium and nickel Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Demilitarization: No | Material: | |
| Cadmium and nickel Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium and nickel Cadmium and nickel Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: | Aluminum alloy | |
| Style Designator:Straight type w/cable clampSurface Treatment:Cadmium and nickelThread Series Designator:UnefShelf Life:N/aUnit Of Measure:Demilitarization:NoFiig: | Surface Treatment: | |
| Straight type w/cable clamp Surface Treatment: Cadmium and nickel Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: | Cadmium and nickel | |
| Surface Treatment: Cadmium and nickel Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Demilitarization: No | Style Designator: | |
| Cadmium and nickel Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Demilitarization: No | Straight type w/cable clamp | |
| Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: | Surface Treatment: | |
| Unef Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: | Cadmium and nickel | |
| Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | Thread Series Designator: | |
| N/a Unit Of Measure: Demilitarization: No Fiig: | Unef | |
| Unit Of Measure: Demilitarization: No Fiig: | Shelf Life: | |
| Demilitarization: No Fiig: | N/a | |
| Demilitarization: No Fiig: | Unit Of Measure: | |
| No Fiig: | | |
| Fiig: | Demilitarization: | |
| | No | |
| | | |
| | A10100 | |