NSN 5935-01-133-1157

Body Style:

Shell Material: Aluminum alloy

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-133-1157

Straight shape
Overall Length:
1.625 inches
Overall Height:
3.110 inches
Overall Width:
2.500 inches
Environmental Protection:
Humidity resistant and salt water resistant and shock resistant and thermal shock resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
0.120 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
2.784 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.437 inches
Distance From Mounting Shoulder To Front Face:
0.766 inches
Mating End Quantity:
2
Contact Removability:
Removable all mating ends single contact grouping
Polarization Method:
3 polarization posts
Shell Type:
Solid
Terminal Location:
Back all mating ends single contact grouping
Contact Material:
Copper alloy all mating ends single contact grouping
Contact Surface Treatment:
Gold all mating ends single contact grouping
Insert Material:
Plastic diallyl phthalate all mating ends or plastic epoxy all mating ends or plastic phenolic all mating ends
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response all mating ends single contact grouping
Terminal Type:
Crimp all mating ends single contact grouping
Guide Design And Location:
Hexagon shape male post left-hand at 12 oclock and hexagon shape male post center at 12 oclock and hexagon shape male post
right-hand at 12 oclock

NSN 5935-01-133-1157

Electrical Receptacle Connector - Page 2 of 2



~ ! !!				
Shell	Surta	ice Tr	eatm	ent:

Cadmium and chromate

Shell Surface Treatment Specification:

Qq-p-416 federal specification all treatment responses

Shell Material Specification:

Qq-a-591 federal specification single material response or qq-a-367 federal specification single material response or qq-a-250 federal specification single material response

Insert Material Specification:

Mil-m-14 military specification single material response all mating ends or 1288 bx mfr ref single material response all mating ends

Included Contact Type:

Round socket all mating ends single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.248 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.