

View Online at <https://aerobasegroup.com/nsn/5935-01-133-4902>

**Body Style:**

Straight type

**Overall Length:**

6.400 inches

**Overall Height:**

0.637 inches

**Overall Width:**

0.350 inches

**Environmental Protection:**

Shock resistant and humidity resistant and corrosion resistant and vibration resistant and thermal shock resistant

**Distance Between Mounting Facility Centers:**

6.150 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

3 rows of contacts non-inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

**Polarization Method:**

Guide pin/socket

**Connector Locking Method:**

Friction

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, cl 1, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2 federal specification 2nd treatment response single mating end single contact grouping

**Terminal Type:**

Pin single mating end single contact grouping

**Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping

**Guide Design And Location:**

D shape socket left-hand at 3 o'clock and d shape socket right-hand at 3 o'clock

**Insert Material Specification:**

Mil-p-19833 military specification single material response single mating end or mil-m-14f military specification single material response single mating end

**Included Contact Quantity:**

160 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.160 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.