## NSN 5935-01-133-5888

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-133-5888

**Body Style:** 

Straight edge type w/mounting flange

**Overall Length:** 

5.835 inches

**Overall Height:** 

0.860 inches

**Overall Width:** 

0.350 inches

**Unthreaded Mounting Hole Diameter:** 

0.125 inches

**Distance Between Mounting Facility Centers:** 

5.575 inches

**Board Accommodated Length:** 

5.100 inches single board

**Board Accommodated Width:** 

0.062 inches

**Mating End Quantity:** 

**Contact Position Arrangement Style:** 

2 rows of independent contacts inserted board single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

3.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:** 

600.0 single mating end single contact grouping

**Connector Locking Method:** 

Friction

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and copper single mating end single contact grouping

**Insert Material:** 

Glass single mating end and plastic diallyl phthalate single mating end

**Terminal Type:** 

Tab, solder lug single mating end single contact grouping

**Insert Material Specification:** 

Mil-m-14, type sdg-f military specification single material response single mating end

**Included Contact Quantity:** 

50 single mating end single contact grouping

## NSN 5935-01-133-5888

Electrical Receptacle Connector - Page 2 of 2



Included	Contact	Type:
----------	---------	-------

Bifurcated accordian leaf spring single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.050 gold grains, troy

**Precious Material:** 

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.