# NSN 5935-01-133-6631

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-133-6631

**Body Style:** 

Straight shape w/screw locks

**Overall Length:** 

1.350 inches

**Overall Height:** 

0.665 inches

**Overall Width:** 

0.250 inches

**Mating End Quantity:** 

,

#### **Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

#### **Contact Removability:**

Nonremovable single mating end single contact grouping

### **Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

#### **Polarization Method:**

Jackscrew

# **Connector Locking Method:**

Jackscrew-socket

# **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

#### **Contact Surface Treatment:**

Gold single mating end single contact grouping

# **Insert Material:**

Plastic polyphenylene single mating end

#### **Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping

# **Terminal Type:**

Solder well single mating end single contact grouping

# **Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping

#### **Insert Material Specification:**

Mil-m-24519 military specification single material response single mating end

# **Included Contact Quantity:**

16 single mating end single contact grouping

# **Included Contact Type:**

Round socket single mating end single contact grouping

#### **Special Features:**

Connector shall be furnished without contacts 5, 6, 14, and 16

# NSN 5935-01-133-6631

Electrical Plug Connector - Page 2 of 2



<b>Precious Material And Location:</b>
Contact surfaces gold
Precious Material And Weight:
0.016 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.