NSN 5935-01-133-7276

Solder well single mating end single contact grouping

Electrical Receptacle Connector - Page 1 of 2



view Online at https://aerobasegroup.com/hsh/5935-01-133-7276
Thread Class:
2a
Thread Direction:
Right-hand
Overall Length:
0.625 inches
Overall Height:
0.812 inches
Overall Width:
0.223 inches
Unthreaded Mounting Hole Diameter:
0.102 inches
Distance Between Mounting Facility Centers:
0.481 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
Nonstd single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Thready Qty Per Inch (tpi):
36
Thread Size:
0.250 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic polytetrafluoroethylene single mating end
Contact Surface Treatment Specification:
Mil-c-45204, type 1, grade c, class 2 military specification single treatment response single mating end single contact grouping
Terminal Type:

NSN 5935-01-133-7276

Electrical Receptacle Connector - Page 2 of 2



Mil-c-45204 spec.

end single contact grouping or qq-c-530 federal specification single

Contact Material Specification:
Qq-b-626 federal specification single material response single mating end single con-
material response single mating end single contact grouping
Shell Material:
Steel
Shell Surface Treatment:
Gold
Shell Surface Treatment Specification:
Mil-c-45204, type 1, grade c, class 2 military specification single treatment response
Shell Material Specification:
Qq-s-764, class 303 cond a federal specification single material response
Insert Material Specification:
Mil-p-19468 military specification single material response single mating end
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Coaxial socket single mating end single contact grouping
Precious Material And Location:
Contact and body surfaces gold
Precious Material And Weight:
0.105 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Uns
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):