# NSN 5935-01-134-1244

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-134-1244

Thread Class:
2a and 2b
Thread Direction:
Right-hand
Body Style:
Straight shape
Overall Length:
0.875 inches
Overall Height:
0.531 inches
Overall Width:
0.265 inches
Environmental Protection:
Thermal shock resistant and humidity resistant and vibration resistant and corrosion resistant and shock resistant
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
14 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
Jackscrew
Connector Locking Method:
Jackscrew-socket
Thready Qty Per Inch (tpi):
56
Thread Size:
0.086 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

## NSN 5935-01-134-1244

Electrical Plug Connector - Page 2 of 2



#### **Contact Material Specification:**

Qq-b-750 federal specification single material response single mating end single contact grouping

### **Insert Material Specification:**

Mil-m-14, typegdi-30f military specification single material response single mating end

### **Included Contact Quantity:**

14 single mating end single contact grouping

### **Included Contact Type:**

Round pin single mating end single contact grouping

## **Precious Material And Location:**

Contact surfaces gold

#### **Precious Material And Weight:**

0.014 gold grains, troy

**Precious Material:** 

Gold

**Thread Series Designator:** 

Unc

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.