Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-134-3528

Thread Class:	
2a	
Thread Direction:	
Right-hand	
Body Style:	
Straight shape, external coupling	
Overall Length:	
Between 1.187 inches and 1.222 inches	
Overall Height:	
Between 1.335 inches and 1.351 inches	
Overall Width:	
Between 1.335 inches and 1.351 inches	
Environmental Protection:	
Moisture proof and salt water resistant and shock proof and vibration proof	
Unthreaded Mounting Hole Diameter:	
Between 0.116 inches and 0.126 inches	
Center To Center Distance Between Mounting Facilities Parallel To Height:	
Between 1.057 inches and 1.067 inches	
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:	
Between 1.057 inches and 1.067 inches	
Distance From Mounting Shoulder To Front Face:	
Between 0.765 inches and 0.775 inches	
Threaded Device Type:	
Back shell	
Mating End Quantity:	
1	
Contact Position Arrangement Style:	
18-38 single mating end	
Contact Removability:	
Removable single mating end single contact grouping	
Polarization Method:	
Keyway or multiple keyway	
Insert Position In Deg:	
120.0 and 161.0 and 225.0 and 336.0	
Shell Type:	
Solid	
Connector Locking Method:	
Bayonet pin	
Thready Qty Per Inch (tpi):	
28	
Thread Size:	
1.125 inches	

Electrical Receptacle Connector - Page 2 of 2



**Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Contact Surface Treatment Specification:** Mil-g-45204, type 1, cl 1 military specification single treatment response single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Aluminum alloy 6061 **Shell Surface Treatment:** Chromium **Shell Material Specification:** Qq-a-367, t6 federal specification single material response **Included Contact Quantity:** 38 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.038 gold grains, troy **Precious Material:** Gold **Test Data Document:** 81349-mil-c-81511 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Thread Series Designator:** Unef **Specification Data:** 81349-mil-c-81511/51 government specification Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.