NSN 5935-01-134-4930

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-134-4930

Body	Styl	e:
------	------	----

Straight shape, thru-hole mount, external coupling

Overall Length:

1.675 inches

Overall Diameter:

0.996 inches

Distance From Mounting Shoulder To Front Face:

0.384 inches

Mounting Facility Thickness:

0.250 inches

Mating End Quantity:

4

Contact Position Arrangement Style:

14-19 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

10.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

315.0

Shell Type:

Solid

Connector Locking Method:

Bayonet latch

Connector Cable Strain Relief Method:

Potting type

Terminal Location:

Back single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Included Contact Quantity:

19 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

NSN 5935-01-134-4930

Electrical Receptacle Connector - Page 2 of 2



N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	

Mil-std (military Standard):

Mil-c-26482 spec.

Shelf Life: