## NSN 5935-01-134-9088

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-134-9088

view Online at https://aerobasegroup.com/hsh/5935-01-134-9088
Overall Length:
1.150 inches
Overall Height:
1.700 inches
Overall Width:
0.978 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
18 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
2000.0 single mating end single contact grouping
Polarization Method:
Polarization boss
Shell Type:
Solid
Connector Locking Method:
Jackscrew
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper single mating end single contact grouping
Contact Surface Treatment:
Copper single mating end single contact grouping and gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
$\label{eq:mil-g-45204} \mbox{Mil-g-45204, type ii, grade $c$ o class $i$ military specification 2nd treatment response single mating end single contact grouping}$
Terminal Type:
Crimp single mating end single contact grouping
Contact Material Specification:
Qq-c-533 federal specification single material response single mating end single contact grouping
Shell Material:
Steel comp 302
Shell Material Specification:

**Insert Material Specification:** 

Qq-s-766 federal specification single material response

Mil-m-14, sdg-f military specification single material response single mating end

## NSN 5935-01-134-9088

Electrical Plug Connector - Page 2 of 2



## **Included Contact Quantity:** 18 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Precious Material And Location:** Contact finish gold **Precious Material:** Gold Shelf Life:

N/a

Demilitarization:

**Unit Of Measure:** 

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.