

View Online at <https://aerobasegroup.com/nsn/5935-01-135-0828>

Body Style:

Straight shape w/clamp

Overall Diameter:

1.938 inches

Environmental Protection:

Corrosion resistant

Cable Entrance Diameter:

Between 0.391 inches and 0.844 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

"3, 6-20" single mating end

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

20.0 single mating end all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

250.0 single mating end all contact groupings

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Connector Locking Method:

Contact twistlock

Connector Cable Strain Relief Method:

Cord grip

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Nickel single mating end all contact groupings

Insert Material:

Plastic polyamide single mating end

Terminal Type:

Tab, solder lug single mating end all contact groupings

Included Contact Quantity:

2 single mating end 1st contact grouping

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0