Electrical Receptacle Connector - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5935-01-135-5527

Thread Class:

2a and 2a

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape, external coupling w/backshell

Overall Length:

1.430 inches

Overall Height:

1.703 inches

Overall Width:

1.703 inches

Environmental Protection:

Humidity resistant and salt water resistant and shock proof and vibration proof

Unthreaded Mounting Hole Diameter:

Between 0.116 inches and 0.125 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.375 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.375 inches

Distance From Mounting Shoulder To Front Face:

0.718 inches

Threaded Device Type:

Back shell and coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

24-61 single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thread Length:

0.290 inches and 0.281 inches

Thready Qty Per Inch (tpi):

18 and 18

NSN 5935-01-135-5527

Electrical Receptacle Connector - Page 2 of 3



Thread Size:	
1.438 inches and 1.56	62 inches
Terminal Location:	
Back single mating er	nd single contact grouping
Contact Material:	
Copper alloy single m	nating end single contact grouping
Contact Surface Tre	atment:
Gold single mating er	nd single contact grouping
Insert Material:	
Plastic epoxy single n	nating end
Contact Surface Tre	atment Specification:
Mil-g-45204, type 1,	cl 2 military specification single treatment response single mating end single contact grouping
Terminal Type:	
Crimp single mating e	and single contact grouping
Shell Material:	
Aluminum alloy	
Shell Surface Treatm	nent:
Nickel	
Shell Material Specif	fication:
Qq-a-367 federal spe	cification single material response
Included Contact Qu	Jantity:
61 single mating end	single contact grouping
Included Contact Ty	/pe:
Round pin single mati	ing end single contact grouping
Precious Material An	nd Location:
Contact surfaces gold	1
Precious Material An	nd Weight:
0.061 gold grains, tro	у
Precious Material:	
Gold	
Test Data Document	t:
81349-mil-c-83723 sp	pecification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes com	nmercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and pe	erformance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Desig	inator:
Unef and unef	
Specification Data:	
81349-mil-c-83723/83	3 government specification
Shelf Life:	
N/a	
Unit Of Measure:	
 Demilitarization:	
No	
Fiig:	



Mil-std (military Standard):

Mil-g-45204 spec.