## NSN 5935-01-136-2352

Thread Class: 2a and 2b

**Thread Direction:** 

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-136-2352

Right-hand and right-hand **Body Style:** Straight shape threaded **Overall Length:** 0.890 inches **Overall Diameter:** 1.750 inches **Distance From Mounting Shoulder To Front Face:** 0.775 inches **Mounting Facility Thickness:** 0.110 inches **Threaded Device Type:** Coupling facility and mounting bushing **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 400pf55 single mating end **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 50.0 Shell Type: Solid **Connector Locking Method:** Externally threaded shell **Thread Size:** 1.625 inches and 1.500 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** 

Solder well single mating end single contact grouping

## NSN 5935-01-136-2352

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Included Contact Quantity:
55 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Round pin single mating end single contact grouping
Thread Series Designator:
Unef and unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A039b0