

View Online at <https://aerobasegroup.com/nsn/5935-01-136-4017>

Body Style:

Straight shape w/clamp

Overall Diameter:

3.312 inches

Environmental Protection:

Heat resistant and salt water resistant

Mating End Quantity:

1

Contact Position Arrangement Style:

4 single mating end

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

20.0 single mating end all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

120.0 single mating end all contact groupings

Polarization Method:

Contact

Connector Locking Method:

Contact twistlock

End Application:

Consolidated space operations center; f117a aircraft; an/fps-124 unattended radar (uar); missile, advanced medium range air-to-air (amraam)/aim120a; support equipment, b-1 aircraft, bath unit, portable; advanced cruise missile, acm-129; electronic shop, trailer, semi mounted, an/asm-189 series; countermeasure set, an/slq-32

Terminal Location:

Side single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Criticality Code Justification:

Feat

Terminal Type:

Screw single mating end all contact groupings

Included Contact Quantity:

3 single mating end 2nd contact grouping

Included Contact Type:

Curved pin w/outside lip single mating end 1st contact grouping

Special Features:

Weapon system essential

Test Data Document:

81348-w-c-596 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81348-w-c-596/137 government specification

Shelf Life:

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0