

View Online at <https://aerobasegroup.com/nsn/5935-01-136-7667>

**Unthreaded Mounting Hole Diameter:**

Between 1.822 inches and 1.866 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

32-2010-10 single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

22.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

500.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

700.0 single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Silver single mating end single contact grouping

**Contact Surface Treatment Specification:**

Mil-c-5015 military specification single treatment response single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium

**Shell Surface Treatment Specification:**

Mil-c-5015 military specification single treatment response

**Included Contact Quantity:**

54 single mating end single contact grouping

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-c-5015 spec.