Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-136-8065

# Body Style:

Straight shape

# **Overall Length:**

0.606 inches

# **Overall Height:**

0.460 inches

# **Overall Width:**

0.238 inches

#### **Environmental Protection:**

Vibration resistant and humidity resistant and salt water resistant and shock resistant

#### Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

2 rows of independent contacts inserted board single mating end

#### **Contact Removability:**

Nonremovable single mating end single contact grouping

# Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

# Contact Maximum Ac Voltage Rating In Volts:

750.0 single mating end single contact grouping

# **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

# **Contact Surface Treatment Specification:**

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal specification 2nd

treatment response single mating end single contact grouping

# **Terminal Type:**

Pin single mating end single contact grouping

### **Contact Material Specification:**

Qq-b-750 federal specification single material response single mating end single contact grouping

#### **Included Contact Quantity:**

12 single mating end single contact grouping

#### **Included Contact Type:**

Round pin single mating end single contact grouping

# **Precious Material And Location:**

Contact surfaces gold

#### **Precious Material And Weight:**

0.012 gold grains, troy

## Precious Material:

Gold

# NSN 5935-01-136-8065

Electrical Plug Connector - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

# Mil-std (military Standard):

Mil-g-45204 spec.

