

View Online at <https://aerobasegroup.com/nsn/5935-01-136-8076>

Body Style:

Straight shape

Overall Length:

1.265 inches

Overall Height:

Between 1.146 inches and 1.170 inches

Overall Width:

Between 3.000 inches and 3.030 inches

Environmental Protection:

Salt spray proof and thermal shock resistant and vibration resistant and shock resistant and moisture resistant and solvent resistant and fuel resistant

Unthreaded Mounting Hole Diameter:

Between 0.195 inches and 0.202 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 0.558 inches and 0.566 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 2.570 inches and 2.580 inches

Distance From Mounting Shoulder To Front Face:

Between 0.615 inches and 0.630 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

"18, 018" single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Mating end and guide pin/socket

Shell Type:

Solid

Connector Locking Method:

Friction

Operating Temperature Rating:

Between -54.0 degrees celsius and 200.0 degrees celsius

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping

Insert Material:

Plastic single mating end and glass single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Contact Material Specification:

Qq-c-533 federal specification single material response single mating end single contact grouping

Guide Design And Location:

D shape pin left-hand bottom at 12 oclock and d shape pin right-hand top at 12 oclock

Shell Material:

Aluminum alloy 380.0

Shell Surface Treatment:

Nickel

Shell Surface Treatment Specification:

Mil-c-26074, cl 3 military specification single treatment response

Shell Material Specification:

Qq-a-591 federal specification single material response

Included Contact Quantity:

18 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.018 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.