

View Online at <https://aerobasegroup.com/nsn/5935-01-137-2273>

Thread Class:

2a and 2b

Thread Direction:

Right-hand

Body Style:

Rectangular shape

Overall Length:

2.855 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 2.276 inches and 2.286 inches

Overall Height:

Between 0.620 inches and 0.735 inches

Environmental Protection:

Humidity resistant and shock resistant and thermal shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

Between 0.123 inches and 0.127 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.761 inches and 0.771 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

75 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

Polarization Method:

Shell and jackscrew

Shell Type:

Solid

Connector Locking Method:

Jackscrew-socket

Thread Length:

0.320 inches

Thready Qty Per Inch (tpi):

32

Thread Size:

0.138 inches

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45294 type 1, grade c military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416 type 2, cl 1 federal specification single treatment response

Insert Material Specification:

Mil-m-14 ty sdg-f military specification single material response single mating end

Shell Guide Type And Location Designator:

C slot

Included Contact Quantity:

75 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Special Features:

Mounting plate

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.075 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-28748 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc

Specification Data:

81349-mil-c-28748/4 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

1-0001-0

Mil-std (military Standard):

Mil-g-45294 spec.