Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-137-6402

Thread Class:
3b
Thread Direction:
Right-hand
Body Style:
Straight shape
Overall Length:
0.954 inches
Overall Height:
2.000 inches
Overall Width:
3.110 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.437 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
2.783 inches
Distance From Mounting Shoulder To Front Face: 0.756 inches
Threaded Device Type:
Mounting hole
Mating End Quantity: 2
Contact Removability:
-
Nonremovable all mating ends all contact groupings Contact Maximum Current Rating In Amps:
Contact Maximum Current Rating in Amos:
7.5 all mating ends 2nd contact grouping
7.5 all mating ends 2nd contact grouping Polarization Method:
<ul> <li>7.5 all mating ends 2nd contact grouping</li> <li>Polarization Method:</li> <li>3 polarization posts</li> </ul>
<ul> <li>7.5 all mating ends 2nd contact grouping</li> <li>Polarization Method:</li> <li>3 polarization posts</li> <li>Shell Type:</li> </ul>
<ul> <li>7.5 all mating ends 2nd contact grouping</li> <li>Polarization Method:</li> <li>3 polarization posts</li> <li>Shell Type:</li> <li>Solid</li> </ul>
7.5 all mating ends 2nd contact grouping Polarization Method: 3 polarization posts Shell Type: Solid Thready Qty Per Inch (tpi):
<ul> <li>7.5 all mating ends 2nd contact grouping</li> <li>Polarization Method:</li> <li>3 polarization posts</li> <li>Shell Type:</li> <li>Solid</li> <li>Thready Qty Per Inch (tpi):</li> <li>40</li> </ul>
<ul> <li>7.5 all mating ends 2nd contact grouping</li> <li>Polarization Method:</li> <li>3 polarization posts</li> <li>Shell Type:</li> <li>Solid</li> <li>Thready Qty Per Inch (tpi):</li> <li>40</li> <li>Thread Size:</li> </ul>
<ul> <li>7.5 all mating ends 2nd contact grouping</li> <li>Polarization Method:</li> <li>3 polarization posts</li> <li>Shell Type:</li> <li>Solid</li> <li>Thready Qty Per Inch (tpi):</li> <li>40</li> <li>Thread Size:</li> <li>0.112 inches</li> </ul>
7.5 all mating ends 2nd contact grouping Polarization Method: 3 polarization posts Shell Type: Solid Thready Qty Per Inch (tpi): 40 Thread Size: 0.112 inches Terminal Location:
7.5 all mating ends 2nd contact grouping Polarization Method: 3 polarization posts Shell Type: Solid Thready Qty Per Inch (tpi): 40 Thread Size: 0.112 inches Terminal Location: Back all mating ends all contact groupings
7.5 all mating ends 2nd contact grouping Polarization Method: 3 polarization posts Shell Type: Solid Thready Qty Per Inch (tpi): 40 Thread Size: 0.112 inches Terminal Location: Back all mating ends all contact groupings
7.5 all mating ends 2nd contact grouping Polarization Method: 3 polarization posts Shell Type: Solid Thready Qty Per Inch (tpi): 40 Thread Size: 0.112 inches Terminal Location: Back all mating ends all contact groupings Contact Material: Copper alloy all mating ends all contact groupings
7.5 all mating ends 2nd contact grouping Polarization Method: 3 polarization posts Shell Type: Solid Thready Qty Per Inch (tpi): 40 Thread Size: 0.112 inches Terminal Location: Back all mating ends all contact groupings Contact Material: Copper alloy all mating ends all contact groupings
7.5 all mating ends 2nd contact grouping Polarization Method: 3 polarization posts Shell Type: Solid Thready Qty Per Inch (tpi): 40 Thread Size: 0.112 inches Terminal Location: Back all mating ends all contact groupings Contact Material: Copper alloy all mating ends all contact groupings Contact Surface Treatment: Gold all mating ends all contact groupings and copper all mating ends all contact groupings
7.5 all mating ends 2nd contact grouping Polarization Method: 3 polarization posts Shell Type: Solid Thready Qty Per Inch (tpi): 40 Thread Size: 0.112 inches Terminal Location: Back all mating ends all contact groupings Contact Material: Copper alloy all mating ends all contact groupings

Electrical Receptacle Connector - Page 2 of 2



# **Contact Surface Treatment Specification:**

Mil-g-45204, type 1, grade c, cl 2 military specification 1st treatment response all mating ends all contact groupings and mil-c-14550 military

specification 2nd treatment response all mating ends all contact groupings

# Criticality Code Justification:

Feat

# **Terminal Type:**

Solder well all mating ends all contact groupings

# **Guide Design And Location:**

D shape pin left-hand at 12 oclock and d shape pin right-hand at 12 oclock

#### **Shell Material:**

Aluminum alloy

# Shell Surface Treatment:

Cadmium and chromate

# Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification 1st treatment response

# **Shell Material Specification:**

Qq-a-591, comp a federal specification single material response

# **Insert Material Specification:**

Mil-p-19833, ty gdi-30f military specification single material response all mating ends

### Included Contact Type:

Round socket all mating ends all contact groupings

# **Special Features:**

6 threaded mtg holes

# Precious Material And Location:

Contact surfaces gold

# **Precious Material And Weight:**

0.268 gold grains, troy

#### **Precious Material:**

Gold

# Thread Series Designator:

Unc

### Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

No

# Fiig:

A039b0

# Mil-std (military Standard):

Mil-g-45204 spec.