NSN 5935-01-137-6405

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-137-6405

Body Style:
Straight type
Overall Length:
3.900 inches
Overall Height:
0.705 inches
Overall Width:
0.400 inches
Environmental Protection:
Thermal shock resistant and vibration resistant and shock resistant
Unthreaded Mounting Hole Diameter:
0.120 inches
Distance Between Mounting Facility Centers:
3.650 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
92 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic polyphenylene single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2, cl 1 military specification single treatment response single mating end single contact grouping
Terminal Type:
Pin single mating end single contact grouping
Contact Material Specification:
Qq-c-530 federal specification single material response single mating end single contact grouping or qq-c-533 federal specification single
material response single mating end single contact grouping

Unable To Decode:

Unable to decode and unable to decode

Mil-m-24519 military specification single material response single mating end

Insert Material Specification:

NSN 5935-01-137-6405

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity: 92 single mating end single contact grouping **Included Contact Type:** Flat pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.092 gold grains, troy **Precious Material:** Gold Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.