

View Online at <https://aerobasegroup.com/nsn/5935-01-137-6419>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

0.838 inches

Overall Height:

1.047 inches

Overall Width:

1.047 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration proof

Unthreaded Mounting Hole Diameter:

Between 0.115 inches and 0.130 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.812 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.812 inches

Distance From Mounting Shoulder To Front Face:

Between 0.442 inches and 0.447 inches

Threaded Device Type:

Back shell

Mating End Quantity:

1

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Thready Qty Per Inch (tpi):

24

Thread Size:

0.688 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Nickel

Shell Surface Treatment Specification:

Mil-c-26074 military specification single treatment response

Included Contact Quantity:

10 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.010 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

Specification Data:

96906-ms27497 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-26074 spec.