

View Online at <https://aerobasegroup.com/nsn/5935-01-137-6432>

Thread Class:

2a and 2b and 2a

Thread Direction:

Right-hand and right-hand and right-hand

Body Style:

Straight shape, rectangular

Overall Width:

1.016 inches

Environmental Protection:

Corrosion resistant and moisture resistant and sand resistant and vibration proof

Unthreaded Mounting Hole Diameter:

0.125 inches

Distance Between Mounting Facility Centers:

2.266 inches

Threaded Device Type:

Coupling facility and coupling facility and mounting stud

Mating End Quantity:

1

Contact Position Arrangement Style:

20 20-20 single mating end

Polarization Method:

Jackscrew and shell

Shell Type:

Solid

Connector Locking Method:

Jackscrew-socket

Thready Qty Per Inch (tpi):

32 and 32 and 40

Thread Size:

0.138 inches and 0.138 inches and 0.138 inches

Insert Material:

Plastic diallyl phthalate single mating end or plastic epoxy single mating end

Shell Material:

Aluminum

Shell Surface Treatment:

Anodize and dichromate potassium

Insert Material Specification:

Mil-m-14, type sdg-f military specification single material response single mating end or mil-p-19833, type gdi-30f military specification single material response single mating end

Shell Guide Type And Location Designator:

C pin

Thread Series Designator:

Unc and unc and unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.