

View Online at <https://aerobasegroup.com/nsn/5935-01-137-8548>

**Body Style:**

Wall type

**Environmental Protection:**

Heat resistant

**Distance Between Mounting Facility Centers:**

3.281 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

15.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

125.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

250.0 single mating end single contact grouping

**Connector Locking Method:**

Contact twistlock

**Terminal Location:**

Back corner single mating end single contact grouping

**Contact Material:**

Copper single mating end single contact grouping

**Terminal Type:**

Screw single mating end single contact grouping

**Included Contact Quantity:**

1 single mating end single contact grouping

**Included Contact Type:**

Curved socket single mating end 2nd contact grouping

**Test Data Document:**

81348-wc596 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0