

View Online at https://aerobasegroup.com/nsn/5935-01-137-9037         Body Style:         Straight type         Overall Length:         5.400 inches         Overall Height:         0.655 inches         Overall Height:         0.268 inches         Environmental Protection:         Moisture resistant and vibration resistant         Unthreaded Mounting Hole Diameter:         0.180 inches         Distance Between Mounting Facility Centers:         5.000 inches         Mating End Quantity:         1         Contact Removable single mating and single contact grouping         Contact Removable single mating end single contact grouping         Contact Maximum Current Rating In Amps:         3.0 single mating end single contact grouping         Contact Maximum Current Rating In Amps:         3.0 single mating end single contact grouping         Contact Maximum Current Rating In Amps:         3.0 single mating end single contact grouping         Contact Material:         Copper alloy single mating end single contact grouping         Contact Surface Treatment:         Cold single mating end single contact grouping and nickel single mating end single contact grouping and nickel single mating end single contact grouping and nickel single mating end single contact grouping and nic	NSN 5935-01-137-9037 Electrical Receptacle Connector - Page 1 of 2	AeroBase Group
Straight type         Overall Length:         5.400 inches         Outsiches         Outsiches         Overall Height:         0.850 inches         Overall Width:         0.286 inches         Environmental Protection:         Noisture resistant and vibration resistant         Untreaded Mounting Hole Diameter:         0.180 inches         Distance Between Mounting Facility Centers:         5.000 inches         Matting End Quantity:         1         Contact Removability:         Norenovable single mating end single contact grouping         Contact Maximum Current Rating In Amps:         3.0 single mating end single contact grouping         Contact Maximum Current Rating In Amps:         3.0 single mating end single contact grouping         Contact Maximum Current Rating In Amps:         3.0 single mating end single contact grouping         Contact Material:         Paperalloy single mating end single contact grouping         Contact Surface Treatment:         Paster daluy inthialte single mating end palsic polyamide single mating end single contact grouping and nickel single mating end single contact grouping an	View Online at https://aerobasegroup.com/nsn/5935-01-137-9037	
Overall Length:         5.400 inches         Overall Height:         0.650 inches         Overall Width:         0.286 inches         Overall Width:         0.286 inches         Environmental Protection:         Notsture resistant and vibration resistant         Unthreaded Mounting Hole Diameter:         0.180 inches         Distance Between Mounting Facility Centers:         0.400 inches         Mating End Quantity:         1         Contact Removability:         Nonremovable single mating end single contact grouping         Contact Maximum Current Rating In Amps:         3.0 single mating end single contact grouping         Contact Maximum Current Rating In Amps:         3.0 single mating end single contact grouping         Contact Maximum Current Rating In Amps:         3.0 single mating end single contact grouping         Contact Maximum Current Rating In Amps:         Back single mating end single contact grouping         Contact Material:         Portental Location:         Back single mating end single contact grouping         Contact Surface Treatment:         Postact dily phthalate single mating end phakel single mating end single contact grouping and inkel single mating end single contact grouping and inke	Body Style:	
5.400 inches         Overall Height:         0.650 inches         Overall Widht:         0.286 inches         Durtand Protection:         Moisture resistant and vibration resistant         Untreaded Mounting Hole Diameter:         0.180 inches         Distance Between Mounting Facility Centers:         5.000 inches         Mating End Quantity:         1         Contact Removability:         Nonremovable single mating end single contact grouping         Contact Removability:         1 Auting and single contact grouping         Contact Maximum Current Rating In Amps:         1 Auting and single contact grouping         Contact Maximum Current Rating In Amps:         1 Auting and single contact grouping         Contact Maximum Current Rating In Amps:         1 Auting and single contact grouping         Contact Maximum Current Rating In Amps:         1 Auting and single contact grouping         Contact Maximum Current Rating In Amps:         2 Auting and single contact grouping         Contact Maximum         Contact Maximum         Contact Maximum         Contact Maximum         Contact Maximum         Contact Marinet:         Contact Surface	Straight type	
Overall Height:0.650 inchesOverall Width:0.286 inchesChromental Protection:Misture resistant and vibration resistantOutsree Retween Mounting Facility Centers:0.100 inchesMatting End Quantity:0.000 inchesMatting End Quantity:1Norenovable single mating end single contact groupingContact Maximum Current Rating In Amps:0.010 single mating end single contact groupingForminal Location:1Pack single mating end single contact groupingContact Maximum Current Rating In Amps:1010Portari Surface Treatment:1011121314141515161718<	Overall Length:	
0.650 inches         Dvarall Width:         0.286 inches         Environmental Protection:         Moisture resistant and vibration resistant         Unthreaded Mounting Hole Diameter:         0.100 inches         Distance Between Mounting Facility Centers:         0.000 inches         Mating End Quantity:         1         Contact Removabile mating end single contact grouping         Contact Removabile single mating end single contact grouping         Contact Maximum Current Rating In Amps:         3.0 single mating end single contact grouping         Contact Maximum Gurent Rating In Amps:         3.0 single mating end single contact grouping         Contact Material:         Roaret Material:         Gold single mating end single contact grouping         Contact Material:         Gold single mating end single contact grouping         Contact Material:         Gold single mating end single contact grouping and nickel single mating end single contact grouping         Contact Surface Treatment:         Gold single mating end single contact grouping and nickel single mating end single contact grouping         Horter Material:         Partic dially Inthalate single mating end or plastic polyamide single mating end single contact grouping and nickel single mating end single contact grouping and ni	5.400 inches	
Overall Width:         0.286 inches         Environmental Protection:         Moisture resistant and vibration resistant         Unthreaded Mounting Hole Diameter:         0.180 inches         Distance Between Mounting Facility Centers:         5.000 inches         Mating End Quantity:         1         Contact Removability:         Noremovable single mating end single contact grouping         Contact Maximum Current Rating In Amps:         3.0 single mating end single contact grouping         Contact Maximum Current Rating In Amps:         3.0 single mating end single contact grouping         Contact Maximum Current Rating In Amps:         3.0 single mating end single contact grouping         Contact Maximum Current Rating In Amps:         Back single mating end single contact grouping         Contact Material:         Coper alloy single mating end single contact grouping         Contact Surface Treatment:         Fold single mating end single contact grouping and nickel single mating end         Postact diallyl phthalate single mating end or plastic polyamide single mating end single contact grouping and nickel single mating end single contact grouping and nickel single mating end single contact grouping and ni	Overall Height:	
0.286 inches         Environmental Protection:         Moisture resistant and vibration resistant         Unthreaded Mounting Hole Diameter:         0.180 inches         Distance Between Mounting Facility Centers:         5.000 inches         Mating End Quantity:         1         Contact Removability:         Norremovable single mating end single contact grouping         Contact Maximum Current Rating In Amps:         3.0 single mating end single contact grouping         Contact Maximum Current Rating In Amps:         3.0 single mating end single contact grouping         Contact Maximum Current Rating In Amps:         3.0 single mating end single contact grouping         Contact Maximum Current Rating In Amps:         Back single mating end single contact grouping         Contact Materiai:         Coper alloy single mating end single contact grouping         Contact Surface Treatment:         Plastic diallyl phthalate single mating end or plastic polyamide single mating end single contact grouping end single contact grouping end single contact grouping end plastic polyamide single mating end single contact grouping end plastic polyamide single mating end         Mileg-45204, type 2, grade c, el 1 military specification 1st treatment response single mating end single contact grouping and q-n-290, el 2	0.650 inches	
Environmental Protection:         Moisture resistant and vibration resistant         Unthreaded Mounting Hole Diameter:         0.180 inches         Distance Between Mounting Facility Centers:         5.000 inches         Mating End Quantity:         1         Contact Removability:         Nonremovable single mating end single contact grouping         Contact Maximum Current Rating In Amps:         3.0 single mating end single contact grouping         Terminal Location:         Back single mating end single contact grouping         Contact Material:         Copper alloy single mating end single contact grouping         Gentact Surface Treatment:         Gold single mating end single contact grouping         Partice Treatment:         Pastic diallyl phthalate single mating end r plastic polyamide single mating end single contact grouping and nickel single mating end single contact grouping and nickel single mating end         Insert Material:         Plastic diallyl phthalate single mating end or plastic polyamide single mating end single contact grouping and nickel single mating end single contact grouping end single contact	Overall Width:	
Moisture resistant and vibration resistant Unthreaded Mounting Hole Diameter: 0.180 inches Distance Between Mounting Facility Centers: 5.000 inches Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 3.0 single mating end single contact grouping Contact Maximum Current Rating In Amps: 3.0 single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping and nickel single mating end single contact grouping Contact Surface Treatment Factor Surface Treatment Specification 1st treatment response single mating end single contact grouping and q-n-290, d 2	0.286 inches	
Intereaded Mounting Hole Diameter:         0.180 inches         Distance Between Mounting Facility Centers:         5.000 inches         Mating End Quantity:         1         Contact Removability:         Nonremovable single mating end single contact grouping         Contact Maximum Current Rating In Amps:         3.0 single mating end single contact grouping         Contact Amaximum Current Rating In Amps:         3.0 single mating end single contact grouping         Contact Material:         Poper alloy single mating end single contact grouping         Contact Material:         Gold single mating end single contact grouping         Fortier Location:         Poper alloy single mating end single contact grouping         Contact Material:         Polatic dially enting end single contact grouping and nickel single mating end single contact grouping and nickel single mating end single contact grouping         Plastic dially Iphthalate single mating end or plastic polyamide single mating end         Plastic dially phthalate single mating end or plastic polyamide single mating end single contact grouping and qu-p-290, dl and plastic polyamide single mating end single contact grouping and qu-p-290, dl and plastic polyamide single mating end single contact grouping and plastic polyamide single mating end single contact grouping and plastic polyamide single mating end single contact grouping and plastic polyamide single mating end single contact groupi	Environmental Protection:	
0.180 inches         Distance Between Mounting Facility Centers:         5.000 inches         Mating End Quantity:         1         Contact Removability:         Nonremovable single mating end single contact grouping         Contact Maximum Current Rating In Amps:         3.0 single mating end single contact grouping         Terminal Location:         Back single mating end single contact grouping         Contact Material:         Copper alloy single mating end single contact grouping         Gold single mating end single contact grouping         Insert Material:         Polatic diallyl phthalate single mating end nickel single mating end single contact grouping and nickel single mating end         Plastic diallyl phthalate single mating end or plastic polyamide single mating end         Mil-g-45204, type 2, grade c, cl 1 military specification 1st treatment response single mating end single contact grouping and nq-n-290, cl 2	Moisture resistant and vibration resistant	
Distance Between Mounting Facility Centers:         5.00 inches         Mating End Quantity:         1         Contact Removability:         Nonremovable single mating end single contact grouping         Contact Maximum Current Rating In Amps:         3.0 single mating end single contact grouping         Terminal Location:         Back single mating end single contact grouping         Contact Material:         Copper alloy single mating end single contact grouping         Gottact Surface Treatment:         Gold single mating end single contact grouping and nickel single mating end single contact grouping         Insert Material:         Plastic diallyl phthalate single mating end or plastic polyamide single mating end         Contact Surface Treatment Specification:         Mil-g-45204, type 2, grade c, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2	Unthreaded Mounting Hole Diameter:	
<ul> <li>5.000 inches</li> <li>Mating End Quantity: <ol> <li>Contact Removability:</li> </ol> </li> <li>Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 3.0 single mating end single contact grouping Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping and nickel single mating end single contact grouping Insert Material: Plastic diallyl phthalate single mating end or plastic polyamide single mating end Contact Surface Treatment Specification: Mil-g-45204, type 2, grade c, cl 1 military specification 1st treatment response single mating end single contact grouping and q-n-290, cl 2</li></ul>	0.180 inches	
Mating End Quantity:         1         Contact Removability:         Nonremovable single mating end single contact grouping         Contact Maximum Current Rating In Amps:         3.0 single mating end single contact grouping         Terminal Location:         Back single mating end single contact grouping         Contact Material:         Copper alloy single mating end single contact grouping         Contact Surface Treatment:         Gold single mating end single contact grouping and nickel single mating end single contact grouping         Insert Material:         Plastic diallyl phthalate single mating end or plastic polyamide single mating end         Contact Surface Treatment Specification:         Mating end single contact grouping the atting end single contact grouping end or plastic polyamide single mating end	Distance Between Mounting Facility Centers:	
1         Contact Removability:         Nonremovable single mating end single contact grouping         Contact Maximum Current Rating In Amps:         3.0 single mating end single contact grouping         Terminal Location:         Back single mating end single contact grouping         Contact Material:         Copper alloy single mating end single contact grouping         Contact Surface Treatment:         Gold single mating end single contact grouping and nickel single mating end single contact grouping         Insert Material:         Plastic diallyl phthalate single mating end or plastic polyamide single mating end         Contact Surface Treatment Specification:         Mil-g-45204, type 2, grade c, cl 1 military specification 1st treatment response single mating end single contact grouping and q-n-290, cl 2	5.000 inches	
Contact Removability:         Nonremovable single mating end single contact grouping         Contact Maximum Current Rating In Amps:         3.0 single mating end single contact grouping         Terminal Location:         Back single mating end single contact grouping         Contact Material:         Poper alloy single mating end single contact grouping         Contact Surface Treatment:         Gold single mating end single contact grouping and nickel single mating end single contact grouping         Insert Material:         Postic diallyl phthalate single mating end or plastic polyamide single mating end         Contact Surface Treatment Specification 1st treatment response single mating end single contact grouping and q-n-290, cl 2	Mating End Quantity:	
Nonremovable single mating end single contact groupingContact Maximum Current Rating In Amps:3.0 single mating end single contact groupingTerminal Location:Back single mating end single contact groupingContact Material:Copper alloy single mating end single contact groupingContact Surface Treatment:Gold single mating end single contact grouping and nickel single mating end single contact grouping and nickel single mating end single contact groupingInsert Material:Plastic diallyl phthalate single mating end or plastic polyamide single mating endContact Surface Treatment Specification:Mil-g-45204, type 2, grade c, cl 1 military specification 1st treatment response single mating end single contact grouping and q-n-290, cl 2	1	
Contact Maximum Current Rating In Amps:         3.0 single mating end single contact grouping         Terminal Location:         Back single mating end single contact grouping         Contact Material:         Copper alloy single mating end single contact grouping         Contact Surface Treatment:         Gold single mating end single contact grouping and nickel single mating end single contact grouping         Insert Material:         Plastic diallyl phthalate single mating end or plastic polyamide single mating end         Contact Surface Treatment Specification:         Mil-g-45204, type 2, grade c, cl 1 military specification 1st treatment response single mating end single contact grouping and q-n-290, cl 2	Contact Removability:	
3.0 single mating end single contact grouping         Ferminal Location:         Back single mating end single contact grouping         Contact Material:         Copper alloy single mating end single contact grouping         Contact Surface Treatment:         Gold single mating end single contact grouping and nickel single mating end single contact grouping         Insert Material:         Plastic diallyl phthalate single mating end or plastic polyamide single mating end         Contact Surface Treatment Specification:         Mil-g-45204, type 2, grade c, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2	Nonremovable single mating end single contact grouping	
Terminal Location:         Back single mating end single contact grouping         Contact Material:         Copper alloy single mating end single contact grouping         Contact Surface Treatment:         Gold single mating end single contact grouping and nickel single mating end single contact grouping         Insert Material:         Plastic diallyl phthalate single mating end or plastic polyamide single mating end         Contact Surface Treatment Specification:         Mil-g-45204, type 2, grade c, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2	Contact Maximum Current Rating In Amps:	
<ul> <li>Back single mating end single contact grouping</li> <li>Contact Material:</li> <li>Copper alloy single mating end single contact grouping</li> <li>Contact Surface Treatment:</li> <li>Gold single mating end single contact grouping and nickel single mating end single contact grouping</li> <li>Insert Material:</li> <li>Plastic diallyl phthalate single mating end or plastic polyamide single mating end</li> <li>Contact Surface Treatment Specification:</li> <li>Mil-g-45204, type 2, grade c, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2</li> </ul>	3.0 single mating end single contact grouping	
Contact Material:Copper alloy single mating end single contact groupingContact Surface Treatment:Gold single mating end single contact grouping and nickel single mating end single contact groupingInsert Material:Plastic diallyl phthalate single mating end or plastic polyamide single mating endContact Surface Treatment Specification:Mil-g-45204, type 2, grade c, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2	Terminal Location:	
Copper alloy single mating end single contact groupingContact Surface Treatment:Gold single mating end single contact grouping and nickel single mating end single contact groupingInsert Material:Plastic diallyl phthalate single mating end or plastic polyamide single mating endContact Surface Treatment Specification:Mil-g-45204, type 2, grade c, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2	Back single mating end single contact grouping	
Contact Surface Treatment: Gold single mating end single contact grouping and nickel single mating end single contact grouping Insert Material: Plastic diallyl phthalate single mating end or plastic polyamide single mating end Contact Surface Treatment Specification: Mil-g-45204, type 2, grade c, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2	Contact Material:	
Gold single mating end single contact grouping and nickel single mating end single contact grouping         Insert Material:         Plastic diallyl phthalate single mating end or plastic polyamide single mating end         Contact Surface Treatment Specification:         Mil-g-45204, type 2, grade c, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2	Copper alloy single mating end single contact grouping	
Insert Material:         Plastic diallyl phthalate single mating end or plastic polyamide single mating end         Contact Surface Treatment Specification:         Mil-g-45204, type 2, grade c, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2	Contact Surface Treatment:	
Plastic diallyl phthalate single mating end or plastic polyamide single mating end Contact Surface Treatment Specification: Mil-g-45204, type 2, grade c, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2	Gold single mating end single contact grouping and nickel single mating end single contact grouping	
Contact Surface Treatment Specification: Mil-g-45204, type 2, grade c, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2	Insert Material:	
Mil-g-45204, type 2, grade c, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2	Plastic diallyl phthalate single mating end or plastic polyamide single mating end	
	Contact Surface Treatment Specification:	
	Mil-g-45204, type 2, grade c, cl 1 military specification 1st treatment response single mating end single contact g	rouping and qq-n-290, cl 2
tederal specification 2nd treatment response single mating end single contact grouping	federal specification 2nd treatment response single mating end single contact grouping	
Terminal Type:	Terminal Type:	

Pin single mating end single contact grouping

### **Contact Material Specification:**

Qq-c-533, temper at federal specification single material response single mating end single contact grouping

### **Included Contact Quantity:**

92 single mating end single contact grouping

## Included Contact Type:

Hermaphrodite single mating end single contact grouping

## **Precious Material And Location:**

Contact surfaces gold

### **Precious Material And Weight:**

0.092 gold grains, troy

Electrical Receptacle Connector - Page 2 of 2

AeroBase Group

**Precious Material:** 

Gold

Shelf Life:

N/a

Unit Of Measure:

--

## Demilitarization:

No

Fiig:

A039b0

# Mil-std (military Standard):

Mil-g-45204 spec.