NSN 5935-01-138-0631

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-138-0631

Body Style:

Rectangular shape

Overall Length:

Between 2.740 inches and 2.780 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 2.382 inches and 2.398 inches

Overall Height:

Between 0.355 inches and 0.375 inches

Overall Width:

Between 1.516 inches and 1.556 inches

Environmental Protection:

Humidity resistant and shock resistant and thermal shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

Between 0.147 inches and 0.153 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.873 inches and 0.883 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

25-104 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

Polarization Method:

Contact

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45294 type 1, grade c military specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Insert Material Specification:

Mil-m-14 ty sdg-f military specification single material response single mating end

Included Contact Quantity:

104 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

NSN 5935-01-138-0631

Mil-std (military Standard):

Mil-g-45294 spec.

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.104 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-28748 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-c-28748/5 government specification
Shelf Life:
N/a
Unit Of Measure:
- -
Demilitarization:
No
Fiig:
A039b0