Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-138-0635

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
Between 1.332 inches and 1.382 inches
Overall Height:
Between 1.459 inches and 1.475 inches
Overall Width:
Between 1.459 inches and 1.475 inches
Environmental Protection:
Moisture proof and salt water resistant and shock proof and vibration proof
Unthreaded Mounting Hole Diameter:
Between 0.116 inches and 0.126 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 1.380 inches and 1.390 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 1.380 inches and 1.390 inches
Distance From Mounting Shoulder To Front Face:
Between 0.894 inches and 0.906 inches
Threaded Device Type:
Back shell
Mating End Quantity:
1
Contact Position Arrangement Style:
20-92 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
116.0 and 160.0 and 191.0 and 311.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Thready Qty Per Inch (tpi):
28
Thread Size:
1.250 inches



**Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Contact Surface Treatment Specification:** Mil-g-45204, type 1, cl 1 military specification single treatment response single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Aluminum alloy 6061 **Shell Surface Treatment:** Chromium **Shell Material Specification:** Qq-a-367, t6 federal specification single material response **Included Contact Quantity:** 92 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.092 gold grains, troy **Precious Material:** Gold **Test Data Document:** 81349-mil-c-81511 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Thread Series Designator:** Un **Specification Data:** 81349-mil-c-81511/41 government specification Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A039b0

Mil-std (military Standard):

Mil-g-45204 spec.