NSN 5935-01-138-1120

Electrical Receptacle Connector - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5935-01-138-1120

Thread Class:
2a and 2b and 2a
Thread Direction:
Right-hand and right-hand
Body Style:
Straight type
Overall Length:
2.250 inches
Overall Height:
0.475 inches
Overall Width:
0.341 inches
Environmental Protection:
Moisture resistant and salt water resistant and shock resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
0.096 inches
Distance Between Mounting Facility Centers:
2.000 inches
Threaded Device Type:
Coupling facility and mounting stud
Mating End Quantity:
1
Contact Position Arrangement Style:
51 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Polarization Method:
Jackscrew
Shell Type:
Solid
Solid Connector Locking Method:
Connector Locking Method:
Connector Locking Method: Jackscrew-socket
Connector Locking Method: Jackscrew-socket Thread Length:
Connector Locking Method: Jackscrew-socket Thread Length: 0.160 inches and 0.160 inches and 0.198 inches
Connector Locking Method: Jackscrew-socket Thread Length: 0.160 inches and 0.160 inches and 0.198 inches Thready Qty Per Inch (tpi):

Terminal Location:

Back single mating end single contact grouping

NSN 5935-01-138-1120

Electrical Receptacle Connector - Page 2 of 3



_							
r -	n	+-	rt.	NЛ	ate	rio	
·	OI.	ιca	·ι	IVI	alc	на	ı .

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, grade c, cl 1 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy or steel

Shell Surface Treatment:

Nickel or passivate

Shell Surface Treatment Specification:

Mil-c-26070 military specification single treatment response or qq-p-35 federal specification single treatment response

Shell Material Specification:

Qq-a-591 federal specification single material response or qq-s-766 federal specification single material response

Insert Material Specification:

Mil-m-14, ty sdg-f or ty gdi-30f military specification single material response single mating end

Unable To Decode:

Unable to decode and unable to decode

Included Contact Quantity:

51 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Special Features:

Jackscrew type-male and location-right handandjackscrew type-female and location-left hand

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.051 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc and unc and unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

NSN 5935-01-138-1120

Electrical Receptacle Connector - Page 3 of 3



Mil-std (military Standard):

Mil-g-45204 spec.