NSN 5935-01-138-3801

Electrical Receptacle Connector Body - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-138-3801

Thread Class: 2b **Thread Direction:** Right-hand **Body Style:** Straight shape, rectangular **Overall Length:** Between 0.809 inches and 0.849 inches **Overall Height:** Between 1.340 inches and 1.360 inches **Overall Width:** Between 2.410 inches and 2.430 inches **Environmental Protection:** Humidity resistant and shock resistant and thermal shock resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** Between 0.143 inches and 0.155 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 0.807 inches and 0.817 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 2.040 inches and 2.050 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 80 single mating end **Polarization Method:** Polarization boss **Connector Locking Method:** Post jacksocket **Operating Tempurature Rating:** Between -55.0 degrees celsius and 125.0 degrees celsius Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Insert Material:** Plastic diallyl phthalate glass filled single mating end **Insert Material Specification:** Mil-m-14, type sdg-f military specification single material response single mating end or mil-p-19833, type gdi-30f military specification single material response single mating end

Test Data Document:

81349-mil-c-28748 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

NSN 5935-01-138-3801

Electrical Receptacle Connector Body - Page 2 of 2



Thread Series Designator:
Unf
Specification Data:
81349-mil-c-28748/9 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):

Mil-m-14 spec.