NSN 5935-01-138-3810

Electrical Receptacle Connector Body - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-138-3810 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, rectangular **Overall Length:** 1.740 inches **Overall Height:** Between 1.850 inches and 1.870 inches **Overall Width:** Between 2.865 inches and 2.885 inches **Environmental Protection:** Humidity resistant and shock resistant and thermal shock resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** 0.149 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 1.245 inches and 1.255 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 2.495 inches and 2.505 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 158 single mating end **Polarization Method:** Polarization boss **Connector Locking Method:** Jackscrew **Operating Tempurature Rating:** Between -55.0 degrees celsius and 125.0 degrees celsius Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Insert Material:** Plastic diallyl phthalate glass filled single mating end

Insert Material Specification:

Mil-m-14, type sdg-f military specification single material response single mating end or mil-p-19833, type gdi-30f military specification single material response single mating end

Test Data Document:

81349-mil-c-28748 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain comportal and parformance requirements and test conditions that are aboung as "typical" "average" "" ata)

NSN 5935-01-138-3810

Electrical Receptacle Connector Body - Page 2 of 2



Thread Series Designator:
Unf
Specification Data:
81349-mil-c-28748/9 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):

Mil-m-14 spec.