Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-138-4067

# Thread Class:

2a

**Thread Direction:** 

Right-hand

#### Body Style:

Straight shape, external coupling

#### **Overall Length:**

2.031 inches

#### **Overall Diameter:**

1.250 inches

#### **Threaded Device Type:**

Coupling facility

#### Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

16s-1 single mating end

#### **Contact Removability:**

Removable single mating end single contact grouping

#### Polarization Method:

Keyway or multiple keyway

#### Insert Position In Deg:

280.0

#### Shell Type:

Solid

#### Thread Size:

1.000 inches

#### **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

## Insert Material:

Silicon single mating end

## **Terminal Type:**

Crimp single mating end single contact grouping

# Shell Material:

Aluminum alloy

# Shell Surface Treatment:

Cadmium

# Included Contact Quantity:

7 single mating end single contact grouping

## Included Contact Type:

Round pin single mating end single contact grouping

# NSN 5935-01-138-4067

Electrical Plug Connector - Page 2 of 2



### **Special Features:**

In order to complete the connector assembly, the user must obtain/provide the backshell; standard versions may be ordered as nsn 5935-01-171-1966, p/n m85049/52-1-16w for the straight style, or nsn 5935-01-186-5611, p/n m85049/51-1-16w for the right angle style **Test Data Document:** 

81349-mil-c-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator: Unef Shelf Life: N/a Unit Of Measure: --Demilitarization: No Fiig: A039b0 Mil-std (military Standard): Mil-c-5015 spec.