

View Online at <https://aerobasegroup.com/nsn/5935-01-138-4344>

Body Style:

Straight shape

Overall Length:

0.780 inches

Overall Height:

1.750 inches

Overall Width:

0.210 inches

Environmental Protection:

Corrosion resistant and heat resistant and cold resistant and moisture resistant and shock resistant and vibration resistant

Distance Between Mounting Facility Centers:

0.562 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

7 single mating end

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

5.0 single mating end all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

450.0 single mating end all contact groupings

Contact Maximum Dc Voltage Rating In Volts:

450.0 single mating end all contact groupings

Polarization Method:

Jackscrew

Connector Cable Strain Relief Method:

Cable clamp

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings

Contact Surface Treatment Specification:

Mil-g-45204 military standard single treatment response single mating end all contact groupings

Terminal Type:

Crimp single mating end all contact groupings

Contact Material Specification:

Mil-g-45204 military standard single material response single mating end all contact groupings

Unable To Decode:

Unable to decode and unable to decode

Included Contact Quantity:

7 single mating end all contact groupings

Included Contact Type:

Round socket single mating end all contact groupings

Special Features:

Jackscrew type-female and location-right hand and jackscrew type-male and location-left hand

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.