

View Online at <https://aerobasegroup.com/nsn/5935-01-138-4344>

**Body Style:**

Straight shape

**Overall Length:**

0.780 inches

**Overall Height:**

1.750 inches

**Overall Width:**

0.210 inches

**Environmental Protection:**

Corrosion resistant and heat resistant and cold resistant and moisture resistant and shock resistant and vibration resistant

**Distance Between Mounting Facility Centers:**

0.562 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

7 single mating end

**Contact Removability:**

Nonremovable single mating end all contact groupings

**Contact Maximum Current Rating In Amps:**

5.0 single mating end all contact groupings

**Contact Maximum Ac Voltage Rating In Volts:**

450.0 single mating end all contact groupings

**Contact Maximum Dc Voltage Rating In Volts:**

450.0 single mating end all contact groupings

**Polarization Method:**

Jackscrew

**Connector Cable Strain Relief Method:**

Cable clamp

**Terminal Location:**

Back single mating end all contact groupings

**Contact Material:**

Copper alloy single mating end all contact groupings

**Contact Surface Treatment:**

Gold single mating end all contact groupings

**Contact Surface Treatment Specification:**

Mil-g-45204 military standard single treatment response single mating end all contact groupings

**Terminal Type:**

Crimp single mating end all contact groupings

**Contact Material Specification:**

Mil-g-45204 military standard single material response single mating end all contact groupings

**Unable To Decode:**

Unable to decode and unable to decode

**Included Contact Quantity:**

7 single mating end all contact groupings

**Included Contact Type:**

Round socket single mating end all contact groupings

**Special Features:**

Jackscrew type-female and location-right hand and jackscrew type-male and location-left hand

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.