

View Online at <https://aerobasegroup.com/nsn/5935-01-138-6373>

Thread Class:

2a and 2a

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape, internal coupling

Overall Length:

1.680 inches

Overall Diameter:

0.635 inches

Environmental Protection:

Moisture resistant and vibration resistant

Threaded Device Type:

Coupling facility

Mating End Quantity:

2

Contact Position Arrangement Style:

Smc 2nd mating end

Contact Removability:

Nonremovable all mating ends single contact grouping

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thready Qty Per Inch (tpi):

32 and 24

Thread Size:

0.190 inches and 0.625 inches

Contact Material:

Copper alloy all mating ends single contact grouping

Contact Surface Treatment:

Gold all mating ends single contact grouping

Insert Material:

Plastic polytetrafluoroethylene all mating ends

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response all mating ends single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Gold

Shell Surface Treatment Specification:

Mil-g-45204 military specification single treatment response

Shell Material Specification:

Qq-b-626 federal specification single material response

Insert Material Specification:

Mil-p-19468 military specification single material response all mating ends

Included Contact Quantity:

1 all mating ends single contact grouping

Included Contact Type:

Coaxial socket all mating ends single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.110 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unf and unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.