Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-138-6375

Thread Class
Thread Class:
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
Between 1.023 inches and 1.165 inches
Overall Height:
1.188 inches
Overall Width:
1.188 inches
Environmental Protection:
Corrosion resistant and vibration resistant and shock resistant and explosion proof
Unthreaded Mounting Hole Diameter:
Between 0.148 inches and 0.154 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.906 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.906 inches
Distance From Mounting Shoulder To Front Face:
Between 0.562 inches and 0.578 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
14s-5 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
22.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
200.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
250.0 single mating end single contact grouping
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
0.0
Shell Type:
Solid



### **Connector Locking Method:**

Externally threaded shell

### Thread Length:

0.391 inches

Thready Qty Per Inch (tpi):

10

### Thread Size:

0.875 inches

# **Terminal Location:**

Back single mating end single contact grouping

### **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Silver single mating end single contact grouping

### **Insert Material:**

Rubber single mating end

# **Contact Surface Treatment Specification:**

Qq-s-365 federal specification single treatment response single mating end single contact grouping

### **Terminal Type:**

Solder well single mating end single contact grouping

# Shell Material:

Aluminum alloy

# Shell Surface Treatment:

Anodize

# **Included Contact Quantity:**

5 single mating end single contact grouping

# **Included Contact Type:**

Round pin single mating end single contact grouping

# **Precious Material And Location:**

Contact surfaces silver

# **Precious Material And Weight:**

0.005 silver grains, troy

### **Precious Material:**

Silver

### **Thread Series Designator:**

Double stub

### Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A039b0