Solder well single mating end single contact grouping

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-138-9888

Thread Class:
2a and 2b and 2a
Thread Direction:
Right-hand and right-hand and right-hand
Body Style:
Rectangular shape
Overall Length:
2.750 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.375 inches
Overall Height:
0.757 inches
Overall Width:
1.531 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.875 inches
Threaded Device Type:
Coupling facility and mounting stud
Mating End Quantity:
1
Contact Position Arrangement Style:
25-104 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Jackscrew-socket
Thready Qty Per Inch (tpi):
32 and 32 and 32
Thread Size:
0.164 inches and 0.164 inches and 0.164 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:



Shell Material:	
Metal	
Shell Surface Treatment:	
Cadmium or nickel	
Shell Surface Treatment Specification:	
Qq-p-416 federal specification single treatment response or qq-n-290 federal specif	ication single treatment response
Included Contact Quantity:	
104 single mating end single contact grouping	
Included Contact Type:	
Round pin single mating end single contact grouping	
Precious Material And Location:	
Contact surfaces gold	
Precious Material And Weight:	
0.104 gold grains, troy	
Precious Material:	
Gold	
Thread Series Designator:	
Unc and unc	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A039b0	