Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-139-0930

Body Style:

Right angle type

**Overall Length:** 

6.220 inches

**Overall Width:** 

3.660 inches

**Distance Between Mounting Facility Centers:** 

5.900 inches

Mating End Quantity:

1

#### Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

**Polarization Method:** 

3 polarization posts

**Terminal Location:** 

Side single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and nickel single mating end single contact grouping

#### **Insert Material:**

Plastic diallyl phthalate single mating end

### **Contact Surface Treatment Specification:**

Mil-g-45204 ty ii, grade c, class 1 military specification 1st treatment response single mating end single contact grouping and mil-p-27418 military specification 2nd treatment response single mating end single contact grouping

### **Terminal Type:**

Crimp single mating end single contact grouping

### **Contact Material Specification:**

Qq-b-626 federal specification single material response single mating end single contact grouping or qq-c-530 federal specification single

material response single mating end single contact grouping

### Insert Material Specification:

Mil-m-14 type sdg-f military specification single material response single mating end

### Included Contact Quantity:

160 single mating end single contact grouping

## Included Contact Type:

Round socket single mating end single contact grouping

## Precious Material And Location:

Contact surfaces gold

### **Precious Material And Weight:**

0.160 gold grains, troy

## **Precious Material:**

Gold

Electrical Receptacle Connector - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0

# Mil-std (military Standard):

Mil-g-45204 spec.