

View Online at <https://aerobasegroup.com/nsn/5935-01-139-0935>

Body Style:

Straight shape, external coupling w/strain relief

Overall Length:

1.576 inches

Diameter:

Between 1.109 inches and 1.141 inches

Overall Diameter:

1.281 inches

Environmental Protection:

Corrosion resistant and moisture resistant

Cable Entrance Diameter:

Between 0.427 inches and 0.438 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

36130 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

600.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

850.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Connector Cable Strain Relief Method:

Cable clamp

Operating Temperature Rating:

302.0 degrees fahrenheit

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic epoxy single mating end and glass fiber single mating end

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum

Shell Surface Treatment:

Cadmium and nickel

Included Contact Quantity:

10 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.010 gold grains, troy

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0