## NSN 5935-01-139-1440

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-139-1440

Thread Class:
2a and 2b
Thread Direction:
Left-hand and right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
1.328 inches
Overall Diameter:
1.137 inches
Environmental Protection:
Corrosion resistant and vibration resistant and shock resistant and explosion proof
Threaded Device Type:
Back shell and coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
14s-5 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
22.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
200.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
250.0 single mating end single contact grouping
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling ring
Thread Length:
0.407 inches
Thready Qty Per Inch (tpi):
20 and 10
Thread Size:
0.750 inches and 0.875 inches
Terminal Location:
Back single mating end single contact grouping

## NSN 5935-01-139-1440

A039b0

Electrical Plug Connector - Page 2 of 2



Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Silver single mating end single contact grouping
Insert Material:
Rubber single mating end
Contact Surface Treatment Specification:
Qq-s-365 federal specification single treatment response single mating end single contact grouping
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize
Included Contact Quantity:
5 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.005 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Unef and double stub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: