# NSN 5935-01-139-5421

Electrical Receptacle Connector Body - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-139-5421
Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Rectangular shape center screwlock
Overall Length:
Between 1.665 inches and 1.685 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
Between 1.295 inches and 1.305 inches
Overall Height:
1.420 inches
Overall Width:
Between 0.820 inches and 0.840 inches
Environmental Protection:
Humidity resistant and shock resistant and thermal shock resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
Between 0.143 inches and 0.155 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
20 single mating end
Polarization Method:
Polarization boss
Shell Type:
Solid
Connector Locking Method:
Post jacksocket
Operating Tempurature Rating:
Between -55.0 degrees celsius and 125.0 degrees celsius
Thready Qty Per Inch (tpi):
32
Thread Size:
0.138 inches
Insert Material:
Plastic diallyl phthalate glass filled single mating end

O.138 inches
Insert Material:
Plastic diallyl phthalate glass filled single mating end
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate

## NSN 5935-01-139-5421

Electrical Receptacle Connector Body - Page 2 of 2



### **Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 1 or cl 2 federal specification all treatment responses

### **Insert Material Specification:**

Mil-m-14, ty sdg-f military specification single material response single mating end or mil-p-19833, ty gdi-30f military specification single material response single mating end

### **Test Data Document:**

81349-mil-c-28748 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unc
Specification Data:
81349-mil-c-28748/10 government specification
Shelf Life:
N/a
Unit Of Measure:

**Demilitarization:** 

No Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.