

View Online at <https://aerobasegroup.com/nsn/5935-01-140-0653>

Body Style:

Straight shape

Overall Length:

1.080 inches

Overall Width:

0.208 inches

Environmental Protection:

Vibration resistant and corrosion resistant

Unthreaded Mounting Hole Diameter:

Between 0.089 inches and 0.094 inches

Distance Between Mounting Facility Centers:

0.865 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

21 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

1000.0 single mating end single contact grouping

Shell Type:

Solid

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2 military specification all treatment responses single mating end single contact grouping

Shell Material:

Metal

Shell Surface Treatment:

Nickel

Shell Surface Treatment Specification:

Mil-c-26074, cl 3 military specification single treatment response

Insert Material Specification:

Mil-m-14, ty sdg military specification single material response single mating end

Included Contact Quantity:

21 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.021 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.