## NSN 5935-01-140-1458

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-140-1458 **Body Style:** Straight shape, external coupling **Overall Length:** 1.215 inches **Overall Height:** 1.234 inches **Overall Width:** 1.234 inches **Unthreaded Mounting Hole Diameter:** 0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.969 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.969 inches **Distance From Mounting Shoulder To Front Face:** Between 0.431 inches and 0.462 inches **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 16-8 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** 

Nickel

**Included Contact Quantity:** 

8 single mating end single contact grouping

## NSN 5935-01-140-1458

Electrical Receptacle Connector - Page 2 of 2



## **Included Contact Type:**

Round pin single mating end single contact grouping

## **Test Data Document:**

81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Fiig:

No

A039b0

Mil-std (military Standard):

Mil-c-26482 spec.