NSN 5935-01-140-2887

Thread Class:

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-140-2887

2a
Thread Direction:
Right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
1.234 inches
Overall Diameter:
1.766 inches
Environmental Protection:
Moisture proof and salt water resistant and vibration proof
Threaded Device Type:
Back shell
Mating End Quantity:
1
Contact Position Arrangement Style:
23-55 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
Insert Position In Deg: 26.0
26.0
26.0 Shell Type:
26.0 Shell Type: Solid
26.0 Shell Type: Solid Connector Locking Method:
26.0 Shell Type: Solid Connector Locking Method: Bayonet latch
26.0 Shell Type: Solid Connector Locking Method: Bayonet latch Thread Length:
26.0 Shell Type: Solid Connector Locking Method: Bayonet latch Thread Length: 0.219 inches
26.0 Shell Type: Solid Connector Locking Method: Bayonet latch Thread Length: 0.219 inches Thready Qty Per Inch (tpi):
Shell Type: Solid Connector Locking Method: Bayonet latch Thread Length: 0.219 inches Thready Qty Per Inch (tpi):
Shell Type: Solid Connector Locking Method: Bayonet latch Thread Length: 0.219 inches Thready Qty Per Inch (tpi): 18 Thread Size:
Shell Type: Solid Connector Locking Method: Bayonet latch Thread Length: 0.219 inches Thready Qty Per Inch (tpi): 18 Thread Size: 1.312 inches
Shell Type: Solid Connector Locking Method: Bayonet latch Thread Length: 0.219 inches Thready Qty Per Inch (tpi): 18 Thread Size: 1.312 inches Terminal Location:
Shell Type: Solid Connector Locking Method: Bayonet latch Thread Length: 0.219 inches Thready Qty Per Inch (tpi): 18 Thread Size: 1.312 inches Terminal Location: Back single mating end single contact grouping
Shell Type: Solid Connector Locking Method: Bayonet latch Thread Length: 0.219 inches Thready Qty Per Inch (tpi): 18 Thread Size: 1.312 inches Terminal Location: Back single mating end single contact grouping Contact Material:
Shell Type: Solid Connector Locking Method: Bayonet latch Thread Length: 0.219 inches Thready Qty Per Inch (tpi): 18 Thread Size: 1.312 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping
Shell Type: Solid Connector Locking Method: Bayonet latch Thread Length: 0.219 inches Thready Qty Per Inch (tpi): 18 Thread Size: 1.312 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment:
Shell Type: Solid Connector Locking Method: Bayonet latch Thread Length: 0.219 inches Thready Qty Per Inch (tpi): 18 Thread Size: 1.312 inches Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping

NSN 5935-01-140-2887Electrical Plug Connector - Page 2 of 2



Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416 federal specification single treatment response
Included Contact Quantity:
55 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.055 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef
Specification Data:
96906-ms27467 government standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.