## NSN 5935-01-140-7223

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-140-7223 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.312 inches **Overall Diameter:** 0.515 inches **Mounting Facility Thickness:** Between 0.046 inches and 0.250 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** Bnc single mating end **Contact Removability:** Removable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Bayonet pin Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thready Qty Per Inch (tpi): 32 Thread Size: 0.375 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Silver single mating end single contact grouping **Insert Material:** Plastic polytetrafluoroethylene single mating end **Terminal Type:** Tab, solder lug single mating end single contact grouping **Shell Material:** 

Zinc

## NSN 5935-01-140-7223

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Nickel
ncluded Contact Quantity:
single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round w/flat
ncluded Contact Type:
Coaxial socket single mating end single contact grouping
Precious Material And Location:
Contact surface silver
Precious Material And Weight:
0.005 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Jnef
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No
Filg:
4039b0