NSN 5935-01-140-7319

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-140-7319

Body Style:
Straight shape
Overall Length:
2.635 inches
Overall Height:
0.660 inches
Overall Width:
0.605 inches
Unthreaded Mounting Hole Diameter:
Between 0.115 inches and 0.125 inches
Distance Between Mounting Facility Centers:
2.406 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
43w2 single mating end
Contact Removability:
Nonremovable single mating end 1st contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Connector Locking Method:
Friction
Terminal Location:
Back single mating end 1st contact grouping
Contact Material:
Copper alloy single mating end 1st contact grouping
Contact Surface Treatment:
Gold single mating end 1st contact grouping and copper single mating end 1st contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2, class 2 military specification 1st treatment response single mating end 1st contact grouping
Terminal Type:
Solder well single mating end 1st contact grouping
Shell Material:
Steel
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification single treatment response

NSN 5935-01-140-7319

Electrical Receptacle Connector - Page 2 of 2



Shell Material Specification:

Qq-s-698 federal specification single material response

Insert Material Specification:

Mil-m-14, type sdg-f or gd1-30f military specification single material response single mating end

Included Contact Quantity:

41 single mating end 1st contact grouping

Included Contact Type:

Round pin single mating end 1st contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.041 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.